



Optic Twinkle - SU013

PRODUCT SPECIFICATIONS

PRODUCT TYPE:	Carpet Tile
CONSTRUCTION:	Tufted
SURFACE APPEARANCE:	Textured Patterned Loop
GAUGE:	1/12" (47.00 rows per 10 cm)
TUFTED WEIGHT:	15 oz/yd ² (509 g/m ²)
PILE THICKNESS:	.082" (2.08 mm)
STITCHES PER INCH:	12.5 (49.21 per 10 cm)
DYE METHOD:	100% Solution Dyed
FIBER TYPE:	Colorstrand® SD Nylon
STAIN RELEASE TECHNOLOGY:	Mohawk Protection Plus Stain
SOIL RELEASE TECHNOLOGY:	Mohawk Protection Plus Soil
DENSITY:	6,673
WEIGHT DENSITY:	101,429
PRIMARY BACKING:	Non-Woven Synthetic
SECONDARY BACKING:	UltraSet®
RECYCLED CONTENT:	Contains a minimum 39% pre-consumer recycled content by total product weight
INSTALLATION METHOD:	Quarter Turn / Brick Ashlar / Vertical Ashlar / Monolithic / Multi Directional
SIZE:	24" x 24" (.6096 m x .6096 m)
FLAMMABILITY:	ASTM E 648 Class I (Glue Down)
SMOKE DENSITY:	ASTM E 662 Less than 450
STATIC PROPENSITY:	AATCC-134 Under 3.5 KV
IAQ GREEN LABEL PLUS:	1098
CRI APPEARANCE RETENTION TESTING:	Heavy Traffic
WARRANTIES:	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Warranty Lifetime Limited Edge Ravel, Zippering, Delamination, and Dimensional Stability Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Atmospheric Contaminants

*All specifications are subject to normal manufacturing tolerances. 5/16
For additional technical information, please contact Technical Services at **800.833.6954**.*