


Classic Tones — SPA19 PRODUCT SPECIFICATIONS

| Style Name: | Classic Tones SPA19 | |
|--|---|--|
| Plank/Tile Dimensions: | 7.5" x 47.25" x 8mm | |
| Strips Per Plank: | Colors 1 & 2 Multi Wide, others are single appearance | |
| Pieces per Carton: | 7 | |
| Pattern Repeat | 10 | |
| Sq. Ft. per Carton: | 17.18 | |
| Cartons per Pallet: | 60 | |
| Weight per Carton: | 24.83 | |
| Profile: | UniClic® Technology | |
| Surface Appearance: | *Random or Embossed In Register | |
| Finish: | Aluminum Oxide | |
| Finish Rating: | AC4 | |
| Core: | HDF (High Density Fiberboard) | |
| Edges/Ends: | Micro Bevel Edges / Micro Bevel Ends | |
| Attached Underlayment: | No | |
| Warranty: | Limited Lifetime Residential Finish Warranty | |
| Installation Approved. | 5 year Light to Medium Commercial Finish Warranty Floating Only - On, Above or Below Grade | |
| Installation Approved: ASTM E662-09 Smoke Density (Flaming) | Passes - 450 or Less | |
| ASTM E648-10 Radiant Panel | Meets or exceeds Class 1 | |
| ASTM C1028-96 Static Coefficient of Friction | 0.53 Dry | |
| Impact Resistance | Passes Class 4 Heavy Commercial | |
| Cleanability-Stain Resistance | Passes Class 4 Heavy Commercial Nalfa 3.4 | |
| Xenon Light Resistance | Nalfa 3.3 Passes 5.0 Class 4 | |
| Thickness Swell | Nalfa 3.2 Passes Class 4 Heavy Commercial | |
| Radiant Flux | Passes ASTM E648-08 | |
| Static Coefficient of Friction | Nalfa 3.1 Passes Class 4 Heavy Commercial | |
| Surface Bond | Nalfa 3.10 Passes Class 4 Heavy Commercial | |

| Colors | | Quarter Round MQND | Incizo 5 in 1 MINC5 | Incizo Base Stair Nose | New Stair Nose MSNP |
|------------------------|-----|-----------------------|------------------------|---------------------------|------------------------|
| Barnhouse Oak | 01* | MQND-02974 | MINC5-02974 | 5BASE-BASE02 | MSNP-02974 |
| Canyon Echo Oak | 02* | MQND-02975 | MINC5-02975 | 5BASE-BASE02 | MSNP-02975 |
| Honeytone Oak | 03 | MQND-02945 | MINC5-02945 | 5BASE-BASE02 | MSNP-02945 |
| Midday Mocha Oak | 04 | MQND-01683 | MINC5-01494 | 5BASE-BASE02 | MSNP-01494 |
| Cheyenne Rock Oak | 05 | MQND-02973 | MINC5-02973 | 5BASE-BASE02 | MSNP-02973 |
| Chocolate Glazed Maple | 06 | MQND-02899 | MINC5-01056 | 5BASE-BASE02 | MSNP-01056 |



Last Update 2-13-15

We reserve the right without prior notification, to modify specifications, or substitute components as technological advancements or process improvements become available which improve the products performance. Please contact Technical Services at 888-387-9881, option 3 if you have questions regarding these specifications.

All wood and laminate flooring should be protected from intense natural and/or artificial UV light exposure to minimize color change.

Check www.mohawkflooring.com for a copy of our most recent installation instructions before beginning installation.

Complies with California ATCM 93120 (CARB) Emission Requirements
U.S. Lacey Act Compliant
FloorScore Certified*
*Contributes to LEED points