

REVERE



TWO-STEP



SKILLFULLY SET

TWO-STEP AND SKILLFULLY SET

Two-Step features a linear pattern that demonstrates a unique long rolling wrap of colored yarns that display a 'Fade in Fade out' visual. Skillfully Set showcases a weaved visual common to many world cultures, which creates a timeless and handmade visual effect.

TWO-STEP

Product Type	Carpet Tile
Construction	Tufted
Surface Appearance	Textured Patterned Loop
Gauge	1/12" (47.00 rows per 10 cm)
Tufted Weight	15 oz/yd ² (509 g/m ²)
Pile Thickness	.076" (1.93 mm)
Stitches Per Inch	12.5 (49.21 per 10 cm)
Density	7,200
Weight Density	109,440
Dye Method	100% Solution Dyed
Fiber Type	Colorstrand® SD Nylon
Stain Release Technology	Mohawk Protection Plus Stain
Soil Release Technology	Mohawk Protection Plus Soil
Primary Backing	Non-Woven Synthetic
Secondary Backing	UltraSet®
Recycled Content	Contains a minimum of 39% pre-consumer recycled content by total product weight
NSF 140	Gold
Installation Method	Quarter Turn / Brick Ashlar / Vertical Ashlar / Monolithic / Multi Directional
Indoor Air Quality	Green Label Plus Certified # 1098
Size/Width	24" x 24" (.6096 m x .6096 m)
Flammability	ASTM E 648 Class 1 (Glue Down)
Smoke Density	ASTM E 662 Less than 450
Static Propensity	AATCC-134 Under 3.5 KV
Appearance Retention Rating (TARR)	Heavy Traffic
Warranties	Lifetime Limited Wear Warranty Lifetime Limited Edge Ravel, Zippering, Delamination and Dimensional Stability Warranty Lifetime Limited Static Protection Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Atmospheric Contaminants Warranty

SKILLFULLY SET

Product Type	Carpet Tile
Construction	Tufted
Surface Appearance	Textured Patterned Loop
Gauge	1/12" (47.00 rows per 10 cm)
Tufted Weight	15 oz/yd ² (509 g/m ²)
Pile Thickness	.068" (1.72 mm)
Stitches Per Inch	12.5 (49.21 per 10 cm)
Density	8,047
Weight Density	122,144
Dye Method	100% Solution Dyed
Fiber Type	Colorstrand® SD Nylon
Stain Release Technology	Mohawk Protection Plus Stain
Soil Release Technology	Mohawk Protection Plus Soil
Primary Backing	Non-Woven Synthetic
Secondary Backing	UltraSet®
Recycled Content	Contains a minimum of 39% pre-consumer recycled content by total product weight
NSF 140	Gold
Installation Method	Quarter Turn / Brick Ashlar / Vertical Ashlar / Monolithic / Multi Directional
Indoor Air Quality	Green Label Plus Certified # 1098
Size/Width	24" x 24" (.6096 m x .6096 m)
Flammability	ASTM E 648 Class 1 (Glue Down)
Smoke Density	ASTM E 662 Less than 450
Static Propensity	AATCC-134 Under 3.5 KV
Appearance Retention Rating (TARR)	Heavy Traffic
Warranties	Lifetime Limited Wear Warranty Lifetime Limited Edge Ravel, Zippering, Delamination and Dimensional Stability Warranty Lifetime Limited Static Protection Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Atmospheric Contaminants Warranty

Cover: Two-Step Carpet Tile 979 Reflective Symmetry and Skillfully Set Carpet Tile 979 Reflective Symmetry


Two-Step



521
Well Composed



589
Natural Influence



841
Applied Brilliance




858
Innovative Mix



869
Lateral Surface



878
Architectural Element



979
Reflective Symmetry

Skillfully Set



521
Well Composed



589
Natural Influence



841
Applied Brilliance



858
Innovative Mix



869
Lateral Surface



878
Architectural Element



979
Reflective Symmetry

Up to 2,000 sq. yds. available within 10 business days or less

REVERE