

# REVERE



ZERO COOL



THREE WINKS

## ZERO COOL AND THREE WINKS

Sweeping Gestures is a random tactile influence of the beauty of weathering conditions on earthen surfaces creating movement, form and rhythm. This elongated, broken pattern creates a personal statement for any commercial interior. It works perfectly and in tandem with its companion product: Onward Bound.



## ZERO COOL

Product Type	Carpet Tile
Construction	Tufted
Surface Appearance	Textured Patterned Loop
Gauge	1/12" (47.00 rows per 10 cm)
Tufted Weight	17 oz/yd <sup>2</sup> (576 g/m <sup>2</sup> )
Pile Thickness	.088" (2.23mm)
Stitches Per Inch	12.2 (48.03 per 10 cm)
Density	6,055
Dye Method	100% Solution Dyed
Fiber Type	Colorstrand® SD Nylon
Stain Release Technology	Protection Plus Stain
Soil Release Technology	Protection Plus Soil
Primary Backing	Non-Woven Synthetic
Secondary Backing	UltraSet®
Recycled Content	Contains 39% pre-consumer recycled content by total product weight
NSF 140	Gold
Indoor Air Quality	Green Label Plus Certified # 1098
Size	24" x 24" (.6096 m x .6096 m)
Installation Method	Quarter Turn / Monolithic / Brick Ashlar / Vertical Ashlar / Multi Directional
Flammability	ASTM E 648 Class 1 (Glue down) ASTM
Smoke Density	662 Less than 450
Static Propensity	AATCC-134 Under 3.5 KV
Appearance Retention Rating (TARR)	Severe Traffic
Warranties	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Lifetime Limited Edge Ravel, Zippering, Delamination, and Dimensional Stability Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Atmospheric Contaminants

## THREE WINKS


Product Type	Carpet Tile
Construction	Tufted
Surface Appearance	Textured Patterned Loop
Gauge	1/12" (47.00 rows per 10 cm)
Tufted Weight	18 oz/yd <sup>2</sup> (610 g/m <sup>2</sup> )
Pile Thickness	.105" (2.67 mm)
Stitches Per Inch	12.2 (48.03 per 10 cm)
Density	5,074
Dye Method	100% Solution Dyed
Fiber Type	Colorstrand® SD Nylon
Stain Release Technology	Protection Plus Stain
Soil Release Technology	Protection Plus Soil
Primary Backing	Non-Woven Synthetic
Secondary Backing	UltraSet®
Recycled Content	Contains a minimum 39% pre-consumer recycled content by total product weight
NSF 140	Gold
Indoor Air Quality	Green Label Plus Certified # 1098
Size	24" x 24" (.6096 m x .6096 m)
Installation Method	Quarter Turn / Monolithic / Brick Ashlar / Vertical Ashlar / Multi Directional
Flammability	ASTM E 648 Class 1 (Glue Down)
Smoke Density	ASTM 662 Less than 450
Static Propensity	AATCC-134 Under 3.5 KV
Appearance Retention Rating (TARR)	Heavy Traffic
Warranties	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Lifetime Limited Edge Ravel, Zippering, Delamination, and Dimensional Stability Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Atmospheric Contaminants

Cover: Zero Cool Carpet Tile 878 Lasting Impression and Three Winks Carpet Tile 878 Lasting Impression


### Zero Cool



521  
Taking Charge




589  
Integrity Committed




841  
Seize Challenge



858  
Performance Driven



869  
Get Inspired




878  
Lasting Impression




979  
Rare Opportunity

### Three Winks



521  
Taking Charge




589  
Integrity Committed



841  
Seize Challenge



858  
Performance Driven



869  
Get Inspired



878  
Lasting Impression



979  
Rare Opportunity

Up to 2,000 sq. yds. available within 10 business days or less

**REVERE**